



"MIS SISTEM" doo, Starine Novaka 19, 21000 Novi Sad, RS  
m.b.08317704 š.d.51390 PIB: 100453514 PPDV: 132733189

Tel/Fax: 021/512-288, 512-289, 510-232

office@missistem.co.rs  
www.missistem.co.rs

T-rn: 105-31977-31 AIK banka  
T-rn: 370-1820-07 Opportunity banka


**POLJOPRIVREDA**  
**OVLAŠĆENI UVOZNIK I DISTRIBUTER**





Sektor poljoprivreda


**TINAZ - TURSKA**  
**PRIKOLICE**

Važi od 1.01.2009

Proizvod	Naziv	Karakteristike	VPC/EUR
	<b>PRIKOLICA 3,5 TONA</b>	Dimenzije sanduka: 3000 mm x 1920 mm Stranice: 400 mm Felne: 550/16 Gume: 750/16 12 platana Kočioni i hidraulični sistem: Prva Petoletka Težina: 1080 kg	<b>2700</b> + PDV
	<b>PRIKOLICA 8 TONA</b>	Dimenzije sanduka: 4500 mm x 2200 mm Stranice: 600 mm + 400 mm Felne: W 11x 18 Gibnjevi: 80x10x10 Gume: 13.0-65-16 platana Kočioni i hidraulični sistem: Prva Petoletka Težina: 2660 kg	<b>10350</b> + PDV
	<b>PRIKOLICA 10 TONA</b>	Dimenzije sanduka: 5000 mm x 2200 mm Stranice: 600 mm + 500 mm Felne: W 11x 18 Gibnjevi: 80x10x12 Gume: 13.0-65-16 platana Kočioni i hidraulični sistem: Prva Petoletka Težina: 2980 kg	<b>11350</b> + PDV

### ROKOKOSAČICE

	<b>ROTACIONA KOSAČICA 165 SA ZAVESOM</b>	Dužina radna / transportna: 830 / 2760mm Širina radna / transportna: 2860 / 1000 mm Radni zahvat: 1650 mm Radna brzina: 10km/h Radni učinak: 16,5 ha/h Broj radnih tela: 2 Broj noževa: 6 Težina: 360 kg težina sa zavesom: 405 kg P.T.O. brzina izlaznog vratila: 540 o/min	<b>1150</b> + PDV
	<b>ROTACIONA KOSAČICA 165 SA HIDRAULIKOM I ZAVESOM</b>	Dužina radna / transportna: 830 / 2760mm Širina radna / transportna: 2860 / 1000 mm Radni zahvat: 1650 mm Radna brzina: 10km/h Radni učinak: 16,5 ha/h Broj radnih tela: 2 Broj noževa: 6 Težina: 450 kg težina sa zavesom: 495 kg P.T.O. brzina izlaznog vratila: 540 o/min	<b>1350</b> + PDV

	<p><b>PREVRTAČ SENA</b></p>	<p>Radni zahvat: 2200 mm Radna brzina: 8,3km/h Radni učinak: 1,8 ha/h Težina: 170 kg</p>	<p><b>470</b> + <b>PDV</b></p>
---	---------------------------------	--	--